


REMARKS

Entry of the amendments to the specification, claims and abstract before examination of the application is respectfully requested. These claims patentably define over the art of record.

If there are any questions regarding this Preliminary Amendment or the application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket # 095309.55827US).

Respectfully submitted,



Gary R. Edwards
Registration No. 31,824

CROWELL & MORING LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
GRE:kms
357623v1

ABSTRACT OF THE DISCLOSURE

~~The present invention relates to~~ In a control system for a vehicle equipped with an electronically actuable drive train, ~~(21) with a steering system (6), brake system (7) and a drive assembly (4). An~~ an operator control device [(10)] generates a movement vector [(BV)] (from a driver request, ~~and (FW), from which movement vector (BV)~~ a control device [(12)] generates control signals for actuating (SS) with which the drive train, ~~(2) can be actuated. In order to simplify maneuvering, in particular backward travel of the vehicle, a~~ A path computer (13) ~~is provided with~~ calculates a movement path based on ~~from~~ actual position/orientation values ~~which are acquired with an orientation and position determining device (14), and based on~~ from setpoint orientation and position values ~~which can be input~~ [(with)] via a destination-inputting device. ~~(15) for the orientation and position of the vehicle (3), which~~ The movement path is ~~composed of~~ includes a sequence of movement vectors [(BV)] which move the vehicle from its current actual ~~orientation and position~~ orientation/position into the setpoint orientation and position when the drive train [(2)] processes the movement vectors [(BV)] of the movement path. For this purpose, the path computer [(13)] is coupled to the control device [(12)], in addition to the operator control device [(10)], via a common drive train interface [(11)] in order to transmit the movement vectors [(BV)].

(Fig. 1)

Attorney Docket No. 095309.55827US
Marked Up Substitute Specification

VEHICLE CONTROL SYSTEM FOR A VEHICLE

BACKGROUND AND SUMMARY OF THE INVENTION

[0001] This application claims the priority of German patent document 103 22 829.2, filed May 19, 2003 (PCT International Application No. PCT/EP2004/005009), the disclosure of which is expressly incorporated by reference herein.

[0002] The present invention relates to a control system for a vehicle, and in particular ~~[[for]]~~ a combination of a towing vehicle and trailer, ~~having the features of the preamble of claim 1.~~

[0003] German patent document DE 100 32 179 A1 ~~has disclosed such~~ discloses a generic vehicle control system in which the vehicle is equipped with an electronically actuable drive train ~~which~~ that comprises at least one steering system, a brake system and a drive assembly. An operator control device which is permanently installed in the vehicle defines ~~[[here]]~~ an input level via which a vehicle driver can input a driver request and which generates a standardized movement vector from the driver request. A second control device defines a coordination level which generates control signals ~~at the output end from the input end~~ based on an input movement vector, ~~in order~~ to actuate the drive train. ~~In order to~~ To transmit the control signals, the second control device is

coupled to the drive train, which then processes the control signals in order to implement the driver request.

[0004] The known control system is characterized by a high level degree of variability, since input levels which are configured in different ways and coordination levels which are configured in different ways can ~~particularly~~ easily be combined with one another, provided that the driver request is always converted into the control signals by means of the standardized movement vectors.

[0005] In utility vehicles ~~[[,]]~~ (for example trucks), it is necessary to provide a person to give directions (sometimes referred to as a ground guide) ~~is necessary~~ for maneuvering ~~[[,]]~~ ~~preferably for~~ during backward travel, in order to reduce ~~[[a]]~~ the risk of collision between the vehicle and an obstacle. Furthermore, the maneuvering, and especially the backward travel ~~[[,]]~~ is particularly difficult in the case of a combination of a towing vehicle and trailer, ~~is particularly difficult~~ ~~owing~~ due to the given kinematic coupling.

[0006] The requirement ~~[[of]]~~ for a person to give directions is extremely disruptive in the case of a truck from ~~[[the]]~~ an economic point of view, since when the truck is in operation it mainly fulfills a transportation function in which there is no need for a person to give directions. In comparison, ~~and~~ ~~compared to this~~ maneuvering ~~has to be~~ is carried out only for a very short part of its operating time, and there ~~There is therefore the desire~~ an incentive to eliminate the necessity for a person to give directions.

[0007] ~~[[The]]~~ One object of the present invention is ~~concerned with the~~
~~problem of specifying, for to provide~~ a control system of the type mentioned
~~above, at the beginning, an improved embodiment~~ which in particular simplifies
the maneuvering of the vehicle.

~~This problem is solved according to the invention by means of the subject matter~~
~~of the independent claim. Advantageous embodiments are the subject matter of~~
~~the dependent claims.~~

[0008] This and other objects and advantages are achieved by the control
system according to the invention, which ~~The invention~~ is based on the general
idea of using a path computer to calculate a movement path. The path computer
provides ~~which makes available~~ a sequence of movement vectors which, when
~~they are~~ processed, move the vehicle from a starting position to a destination
position. The starting position can be defined here by actual values for the
current orientation and position of the vehicle, ~~which values can be~~ determined
using a suitable orientation- and position-determining device. For the
destination position, setpoint values for the orientation and position of the
vehicle are used which can be predefined using a destination-inputting device. ~~It~~
~~is of particular significance here that the~~

[0009] The path computer transmits the acquired movement vectors to the
second control device via ~~[[a]]~~ the same drive train interface ~~to the control device~~
~~via~~ by which the operator control device, which is fixed to the vehicle, also
transmits the movement vectors to the second control device. ~~During the~~

~~calculation of~~ In calculating the movement path, the path computer can take into account the kinematic and dynamic properties of the vehicle. This is achieved by guiding the vehicle ~~being-guided~~ along an optimum[[,]] (in particular risk-free) movement path. The maneuvering of the vehicle can be automated by predefining the setpoint values, and by monitoring the actual values and can be considerably simplified for the driver. ~~In particular~~ Significantly, a person to give directions can be dispensed with.

[0010] In one advantageous development, the path computer is designed to calculate such a movement path in which the vehicle is traveling backward or which contains at least one movement path section in which the vehicle travels backward. This embodiment [[has a]] is particularly advantageous ~~effect if the vehicle is for~~ a combination of a towing vehicle (sometimes referred to as tractor) and a trailer, since the backward travel of a combination is ~~extremely~~ difficult and time-consuming even for experienced drivers. By calculating the backward travel and processing the necessary movement vectors, ~~which are necessary for this~~ it is possible for the vehicle generally to reach the desired destination position at the first attempt with the control system according to the invention.

[0011] Other objects, advantages and novel features of the present invention will become apparent from the following detailed description of the invention when considered in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

~~Further important features and advantages of the invention emerge from the subclaims, from the drawings and from the associated description of the figures with reference to the drawings.~~

~~It goes without saying that the features which are specified above and the features which are still to be explained below can be used not only in the respectively specified combination but also in other combinations or alone, without departing from the scope of the present invention.~~

~~Preferred exemplary embodiments of the invention are illustrated in the drawings and will be explained in more detail in the following description; identical reference symbols relating to identical or functionally identical or similar components.~~

~~In the drawings, in each case in schematic views:~~

[0012] Fig. 1 is a ~~highly simplified basic outline, in the manner of a circuit diagram, conceptual block diagram~~ of a control system according to the invention; [[,]]

[0013] Fig. 2 is a plan view of a tractor-trailer combination vehicle as a basic illustration; [[,]]

[0014] Fig. 3 is a plan view, as in [[fig.]] Fig. 2, but with another combination vehicle; [[,]] and

[0015] Fig. 4 is a plan view of a combination vehicle as in [[fig.]] Fig. 2, but with sections of the travel path of the vehicle.

DETAILED DESCRIPTION OF THE DRAWINGS

[0016] According to [[fig.]] Fig. 1, a control system 1 according to the invention comprises a drive train 2 of a vehicle 3 ~~which is~~ (shown in [[figs]] Figs. 2 to 4). The control system 1 operates here with an electronically actuatable drive train 2, and can therefore also be referred to as a drive-by-wire system or X-by-wire system. The drive train 2 comprises here a drive assembly 4, a transmission 5, a steering system 6, a brake system 7 and a ride level control device 8. It is apparent that in another embodiment, the drive train 2 can also have more or fewer components 4 to 8. In an electronically actuatable drive train 2 there is no continuous mechanical or hydraulic connection between the individual components 4 to 8 of the drive train 2 and operator control elements 9, which are generally arranged in a cockpit of the vehicle 3. The operator control elements 9, which together form an operator control device 10 of the control system 1, are, for example, an accelerator pedal 9₄, a gearspeed-shifting device 9₅, a steering wheel 9₆, a brake pedal 9₇ and a controlling element 9₈ for the ride level control 8 of the motor vehicle 3.

[0017] By means of the operator control elements 9 it is possible for a vehicle driver to input a driver request FW into the operator control device 10. The operator control device 10 then generates a movement vector BV from the input-side driver request FW, and transmits it ~~transmits said movement vector~~

~~BV at the output end to a drive train interface 11, which . The drive train interface 11 passes on the movement vector BV~~ it to a control device 12. Since the vector is a standardized movement vector BV, the control device 12 can generate control signals SS from the movement vector BV and transmit ~~these control signals SS~~ them to the drive train 2 in a known suitable manner. (See, for example German patent document DE 100 32 179 A1, which is incorporated by reference herein.) The drive train 2 can then process the incoming control signals SS, as a result of which the driver request FW is implemented.

~~With respect to the transmission of signals between the control device 12 and drive train 2 or its components 4 to 8, reference is made otherwise to the abovementioned DE 100 32 179 A1, whose contents are herewith incorporated by express reference in the disclosed contents of the present invention.~~

[0018] The control system 1 according to the invention also comprises a path computer 13, which is ~~[[also]]~~ connected to the drive train interface 11 and which communicates with an orientation- and position-determining device 14 and with a destination-inputting device 15.

[0019] Actual values for the orientation and position of the vehicle 3 can be continuously determined using the orientation- and position-determining device 14. "Position" is understood here to be the geographic location of the vehicle 3, while "orientation" is understood to be the orientation of a longitudinal direction of the vehicle 3 with respect to a geographic coordinate system, preferably with

respect to the cardinal points. These actual values are transmitted by the orientation- and position-determining device 14 to the path computer 13.

[0020] Setpoint values for the orientation and position of the vehicle 3 can be input into the destination-inputting device 15, and this can be done, for example, manually or in an automated fashion. These setpoint values[[,]] (that is, ~~to say the~~ setpoint orientation and the setpoint position) [[,]] define [[here]] a destination orientation and ~~destination~~ position which the vehicle 3 is to assume at the end of its movement. For example, the vehicle 3 which is embodied as a truck is to be driven up to a loading ramp in such a way that the loading and unloading of the vehicle 3 can be started immediately. The destination-inputting device 15 is coupled to the path computer 13 in order to transmit the setpoint values.

[0021] The path computer 13 is [[then]] configured ~~in such a way that it calculates~~ to calculate a movement path (formed by a sequence of standardized movement vectors BV) based on [[from]] the incoming actual values and the incoming setpoint values, ~~this movement path being formed by a sequence of standardized movement vectors BV~~. The movement path is calculated here in such a way that it moves the vehicle 3 from the actual orientation and the actual position into the setpoint orientation and the setpoint position when the drive train 2 processes the movement vectors BV of the movement path. Since, according to the invention, the path computer 13 is coupled ~~according to the invention~~ to the control device 12 via the drive train interface 11, the control device 12 can convert the movement vectors BV generated by the path computer

13 into control signals SS in accordance with the movement path, and said control signals SS are processed by the drive train 2 exactly as if the movement vectors BV came from the operator control device 10.

[0022] ~~Owing~~ Due to the foregoing design of the control system 1, the path computer 13 can ~~particularly~~ easily be integrated into the control system 1 without increased expenditure ~~being necessary for this purpose~~.

[0023] During the calculation of the movement path, the path computer 13 can take into account vehicle ambient conditions such as, for example, a course of the road in the region of the vehicle 3 and/or a minimum distance of the vehicle 3 from obstacles. In order to ~~be able to~~ convey the vehicle ambient conditions to the path computer 13, an input device 16 can be provided into which the vehicle ambient conditions can be input. In one expedient embodiment, this input device 16 can already be integrated into the destination-inputting device 15. The input devices 15, 16 may be, for example, a keyboard and/or a corresponding reader device. Furthermore, it is possible to provide a sensor system 17 which is configured in such a way that it senses conditions which are predefined in the surroundings of the vehicle 3, such as, for example, the edge of the road and distance values, and transmits them to the path computer 13.

[0024] The orientation- and position-determining device 14 is expediently configured in such a way that it continuously acquires the actual values of the vehicle 3. For example, the actual values of the orientation and position change as the movement vectors BV of the calculated movement path are processed. The

path computer 13 is expediently configured in such a way that it continuously updates and recalculates the movement path by means of the new, current actual values. In this procedure it is sufficient to determine the movement path only relatively roughly at the beginning, and ~~[[only]]~~ to define it more precisely as the destination is approached. By continuously updating the movement path it is also possible to take into account vehicle ambient conditions which additionally come about, or change, during the movement of the vehicle 3.

[0025] Fig. 1 shows a further, specific embodiment in which the control system 1 comprises a transceiver arrangement 18, ~~which is~~ (indicated by a ~~brace~~ bracket), including ~~-This arrangement 18 has~~ at least one transmitter 19 and at least one receiver 20.

[0026] The path computer 13 and the components 14 to 17 which are connected thereto are expediently permanently installed on the vehicle 3. However, in addition or alternatively it is possible to provide an embodiment in which the path computer 13' is arranged, together with its peripherals 14' to 17', at a distance from the vehicle 3. This remote path computer 13' is connected to the transmitter 19 and transmits the movement vectors BV of the movement path to it. The transmitter 19 generates, from the movement vectors BV, remote control signals FS which are received by the receiver 20. The receiver 20 can regenerate the movement vectors BV again from these remote control signals FS and transmit ~~[[said]]~~ this movement vectors to the control device 12 via the drive train interface 11.

[0027] The path computer 13' which can be moved to a remote position and the path computer 13 which is fixed to the vehicle can be used as alternatives or in combination. Furthermore it is apparent that a different configuration of components which are fixed to the vehicle and components which can be moved to a remote position is possible. For example, the path computer 13 can be fixed to a vehicle, while one or more of its peripheral components 14 to 17 are arranged remotely from the vehicle 3 and communicate with the path computer 13 via a suitable transceiver arrangement.

[0028] ~~According to fig. 2,~~ As illustrated in Fig. 2, the control system 1 according to the invention is particularly suitable for a vehicle 3 which is embodied as a combination, including vehicle and which accordingly has a towing vehicle 21 and a trailer 22, the latter being . ~~The embodiment according to fig. 2 is concerned with a combination vehicle 3, in which the trailer 22 is~~ coupled to the towing vehicle 21 via a towbar 23. As an alternative ~~to this,~~ [[fig.]] Fig. 3 shows another combination vehicle 3 in which the trailer 22 is embodied as a semitrailer which is thus coupled to the towing engine or towing vehicle 21 without a towbar.

[0029] ~~Insofar as~~ When the orientation- and position-determining device 14 is ~~a device which is~~ fixed to the vehicle, the ~~vehicle 3~~ latter can be equipped with a satellite navigation receiver 24 in accordance with [[figs]] Figs. 2 and 3. Furthermore, both the towing vehicle 21 and the trailer 22 are each equipped with an electronically readable compass 25 or 26. In the combination vehicle 3 which operates with the towbar 23, a bend angle sensor 27 ~~is also provided and~~

~~said sensor 27~~ determines the bend angle between the towbar 23 and trailer 22.

In addition or alternatively, it is also possible to provide a bend angle sensor which acquires the bend angle between the towbar 23 and the towing vehicle 21. For more details on the method of operation and the structure of the orientation- and position-determining device 14 which is fixed to the vehicle it is possible to refer to German patent document DE 100 31 244 A1, whose content is ~~herewith added to the disclosed content of~~ hereby incorporated by reference into the present invention ~~by express reference~~.

[0030] Alternatively, the orientation- and position-determining device 14 may also be ~~a device which is~~ remote from the vehicle 3, and ~~which operates~~ may operate, for example, as a radar system.

[0031] ~~Insofar as~~ When the vehicle is a combination vehicle 3, the orientation- and position-determining device 14 ~~is constructed in such a way that it~~ can be used to determine the actual values for the orientation and position both of the towing vehicle 21 and of the trailer 22. Furthermore, the destination-inputting device 15 is then configured in such a way that the setpoint values for the orientation and position of the towing vehicle 21 and/or of the trailer 22 can be input.

[0032] With reference to ~~[[fig.]]~~ Fig. 4, a description will now be given of a specific application ~~[[case]]~~ for which the control system 1 according to the invention is particularly suitable.

[0033] Fig. 4 shows a detail of a site 28 of a loading station, in particular of a freight yard. On this site 28 there is at least one loading ramp 29 which has to be approached by a combination vehicle 3, for example, in such a way that the rear end 30 of the trailer 22 is positioned approximately in front of the loading ramp 29. However, only a relatively small holding bay 31, into which the trailer 22 must be driven backward, is located in front of the loading ramp 29.

[0034] The optimum destination position of the trailer 22 in the holding bay 31 on the ramp 29 thus constitutes the predefined destination from which the setpoint values for the orientation and position of the trailer 22 can be derived. The setpoint orientation and the setpoint position are expediently known and can be conveyed to the path computer 13 via the destination-inputting device 15. The combination vehicle 3 is located [[here]] at any desired point on the site 28, while the towing vehicle 21 and trailer 22 can have any desired orientations. The path computer 13 receives precise knowledge about the actual values of the orientation and position of the towing vehicle 21 and of the trailer 22 via the orientation- and position-determining device 14. The path computer 13 then calculates a movement path for the combination vehicle 3, whose movement vectors BV can be processed in particular automatically. It is clear here that the movement vectors BV of the drive assembly 4 of the drive train 2 are expediently actuated only in such a way that the combination vehicle 3 moves relatively slowly, in particular at walking pace.

[0035] As is apparent from [[fig.]] Fig. 4, the movement path can contain a movement path section 32 (illustrated by a broken line) in which the combination

vehicle 3 travels backward. In fig. 4, a movement path section 32 in which the combination vehicle 3 is traveling backward is illustrated by a broken line. The individual points 33 ~~which are arranged~~ along the movement path section 32 symbolize ~~[[here]]~~ the structure of the movement path which is composed of parts of the movement path which are arranged in series one next to the other.

[0036] Provided that the original position of the combination vehicle 3 is suitable for directly approaching the destination position for the trailer 22 in the holding bay 31, this can be readily implemented by automating the vehicle movement. The maneuvering and in particular the backward travel of the combination vehicle 3 can thus be carried out in a very efficient way. However, if the original position of the combination vehicle 3 is not suitable for directly driving into the destination position in the holding bay 31, according to one embodiment of the invention the path computer 13 ~~can be~~ is configured, ~~in one development,~~ in such a way that before the backward travel the movement path generates ~~an amount~~ a section of forward travel 34 corresponding to the movement path section 32, and said forward travel 34 moves the combination vehicle 3 from an unfavorable original position into a favorable intermediate position from which the combination vehicle 3 can be moved directly by means of backward travel 32 in such a way that its trailer 22 moves with the desired orientation into the holding bay 31 as far as the loading ramp 29.

[0037] The sensor system 17 can be installed fixed to the vehicle and may comprise, for example, distance-measuring sensors. In the embodiment explained with reference to ~~[[fig.]]~~ Fig. 4, it may be expedient to provide sensors which are

positionally fixed and which sense, for example, the approaching of the trailer 22 to the loading ramp 29.

[0038] The operator control device 10 can be connected via radio to the drive train interface 11 or to the path computer 13 so that the vehicle can be remote-controlled. On the other hand, the operator control device 10 can also be coupled directly to the path computer 13 via a transmission line for the transmission of signals.

[0039] The foregoing disclosure has been set forth merely to illustrate the invention and is not intended to be limiting. Since modifications of the disclosed embodiments incorporating the spirit and substance of the invention may occur to persons skilled in the art, the invention should be construed to include everything within the scope of the appended claims and equivalents thereof.